



# Jet Black Color Magic Black

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations  
US GHS SDS

Revision Date: 04/01/2024

Date of Issue: 07/15/2021

Supersedes Date: 10/25/2021

Version: 1.2

## SECTION 1: IDENTIFICATION

### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** Jet Black Color Magic Black

**Product Code:** T-374KTR (50258)

**Formula:** 40765

### 1.2. Intended Use of the Product

**Use of the Substance/Mixture:** Automotive Wax/Polish/Sealant/Glaze - All Other Forms

### 1.3. Name, Address, and Telephone of the Responsible Party

#### Manufacturer

Turtle Wax, Inc.

948 Springer Dr.

Lombard, IL 60148

Phone Number: 1(630)455-3700

Toll-Free Number: 1(800)887-8539

### 1.4. Emergency Telephone Number

**Emergency Number** : Velocity EHS  
1-800-255-3924 (US and Canada)  
1-813-248-0585 (International)

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

Carc. 2 H351

Full text of hazard classes and H-statements : see section 16

### 2.2. Label Elements

#### GHS-US Labeling

**Hazard Pictograms (GHS-US)**



GHS08

**Signal Word (GHS-US)**

: Warning

**Hazard Statements (GHS-US)**

: H351 - Suspected of causing cancer.

**Precautionary Statements (GHS-US)**

: P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P280 - Wear protective gloves, protective clothing, and eye protection.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

# Jet Black Color Magic Black

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

US GHS SDS

### 3.2. Mixture

Name	Synonyms	Product Identifier	%*	GHS US classification
White mineral oil, petroleum	Mineral Oil / White mineral oil / Oils, white mineral, petroleum / White mineral oil (petroleum)	(CAS-No.) 8042-47-5	4	Not classified
Aluminum oxide (Al <sub>2</sub> O <sub>3</sub> )	Alumina / Aluminum oxide / .alpha.- Alumina / Aluminium oxide	(CAS-No.) 1344-28-1	> 1.98	Not classified
Carbon black	C.I. 77266 / C.I. Pigment Black 6 / C.I. Pigment Black 7 / Lampblack	(CAS-No.) 1333-86-4	0.375 – 0.525	Acute Tox. 4 (Inhalation:dust,mist), H332 Carc. 2, H351 Comb. Dust
Titanium dioxide	C.I. 77891 / C.I. Pigment White 6 / Titanium oxide (TiO <sub>2</sub> )	(CAS-No.) 13463-67-7	0.013 – 0.221	Not classified
Isopropyl alcohol	2-Hydroxypropane / 2-Propyl alcohol / 2-Propanol / Isopropanol	(CAS-No.) 67-63-0	0.075 – 0.15	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Sodium hydroxide	Caustic soda / Sodium hydroxide (Na(OH)) / SODIUM HYDROXIDE / LYE	(CAS-No.) 1310-73-2	0.0075 – 0.0105	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402
Cyclohexane	CYCLOHEXANE / Benzene, hexahydro- / Hexahydrobenzene	(CAS-No.) 110-82-7	0.00022 – 0.0011	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Ethyl acetate	Acetic acid, ethyl ester / Ethyl ethanoate / ETHYL ACETATE	(CAS-No.) 141-78-6	≤ 0.00022	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Acrylic acid	Acroleic acid / Propenoic acid / 2-Propenoic acid	(CAS-No.) 79-10-7	≤ 0.00022	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

\*The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200].

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First-aid Measures

**First-aid Measures General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**First-aid Measures After Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**First-aid Measures After Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 5 minutes. If exposed or concerned: Get medical advice/attention.

**First-aid Measures After Eye Contact:** Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

**First-aid Measures After Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

# Jet Black Color Magic Black

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
US GHS SDS

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**Symptoms/Injuries:** Suspected of causing cancer.

**Symptoms/Injuries After Inhalation:** Prolonged exposure may cause irritation.

**Symptoms/Injuries After Skin Contact:** Prolonged exposure may cause skin irritation.

**Symptoms/Injuries After Eye Contact:** May cause slight irritation to eyes.

**Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** Suspected of causing cancer.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Water spray, fog, carbon dioxide (CO<sub>2</sub>), alcohol-resistant foam, or dry chemical.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Silicon oxides.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Ventilate area.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

### 7.3. Specific End Use(s)

Automotive Wax/Polish/Sealant/Glaze - All Other Forms

# Jet Black Color Magic Black

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
US GHS SDS

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Cyclohexane (110-82-7)		
USA ACGIH	ACGIH OEL TWA [ppm]	100 ppm
USA NIOSH	NIOSH REL (TWA)	1050 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL TWA [ppm]	300 ppm
USA IDLH	IDLH [ppm]	1300 ppm (10% LEL)
USA OSHA	OSHA PEL (TWA) [1]	1050 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) [2]	300 ppm
Ethyl acetate (141-78-6)		
USA ACGIH	ACGIH OEL TWA [ppm]	400 ppm
USA NIOSH	NIOSH REL (TWA)	1400 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL TWA [ppm]	400 ppm
USA IDLH	IDLH [ppm]	2000 ppm (10% LEL)
USA OSHA	OSHA PEL (TWA) [1]	1400 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) [2]	400 ppm
Acrylic acid (79-10-7)		
USA ACGIH	ACGIH OEL TWA [ppm]	2 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen, Skin - potential significant contribution to overall exposure by the cutaneous route
USA NIOSH	NIOSH REL (TWA)	6 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL TWA [ppm]	2 ppm
Titanium dioxide (13463-67-7)		
USA ACGIH	ACGIH OEL TWA	10 mg/m <sup>3</sup>
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (TWA)	2.4 mg/m <sup>3</sup> (CIB 63-fine) 0.3 mg/m <sup>3</sup> (CIB 63-ultrafine, including engineered nanoscale)
USA IDLH	IDLH	5000 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m <sup>3</sup> (total dust)
Aluminum oxide (Al <sub>2</sub> O <sub>3</sub> ) (1344-28-1)		
USA ACGIH	ACGIH OEL TWA	10 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
Sodium hydroxide (1310-73-2)		
USA ACGIH	ACGIH OEL Ceiling	2 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (Ceiling)	2 mg/m <sup>3</sup>
USA IDLH	IDLH	10 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) [1]	2 mg/m <sup>3</sup>
White mineral oil, petroleum (8042-47-5)		
USA ACGIH	ACGIH OEL TWA	5 mg/m <sup>3</sup> (mist)
Carbon black (1333-86-4)		
USA ACGIH	ACGIH OEL TWA	3 mg/m <sup>3</sup> (inhalable particulate matter)
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA NIOSH	NIOSH REL (TWA)	3.5 mg/m <sup>3</sup> 0.1 mg/m <sup>3</sup> (Carbon black in presence of Polycyclic aromatic hydrocarbons)
USA IDLH	IDLH	1750 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) [1]	3.5 mg/m <sup>3</sup>
Isopropyl alcohol (67-63-0)		
USA ACGIH	ACGIH OEL TWA [ppm]	200 ppm
USA ACGIH	ACGIH OEL STEL [ppm]	400 ppm

# Jet Black Color Magic Black

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

US GHS SDS

<b>USA ACGIH</b>	ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>USA ACGIH</b>	BEI (BLV)	40 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift at end of workweek (background, nonspecific)
<b>USA NIOSH</b>	NIOSH REL (TWA)	980 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL TWA [ppm]	400 ppm
<b>USA NIOSH</b>	NIOSH REL (STEL)	1225 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL STEL [ppm]	500 ppm
<b>USA IDLH</b>	IDLH [ppm]	2000 ppm (10% LEL)
<b>USA OSHA</b>	OSHA PEL (TWA) [1]	980 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) [2]	400 ppm

### 8.2. Exposure Controls

#### Appropriate Engineering Controls

: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

#### Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



#### Materials for Protective Clothing

: Chemically resistant materials and fabrics.

#### Hand Protection

: Wear protective gloves.

#### Eye and Face Protection

: Chemical safety goggles.

#### Skin and Body Protection

: Wear suitable protective clothing.

#### Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

#### Other Information

: When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Black, viscous liquid
Odor	: Typical solvent
Odor Threshold	: No data available
pH	: 8
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: > 93 °C (199.4 °F) (Closed-Cup)
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: 1.019 (Water=1)
Solubility	: No data available
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: 4300 cP

### 9.2. Other Information

No additional information available

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity: Hazardous reactions will not occur under normal conditions.

# Jet Black Color Magic Black

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
US GHS SDS

- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Thermal decomposition may produce: Carbon oxides (CO, CO<sub>2</sub>). Silicon oxides.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects

**Acute Toxicity (Oral):** Not classified

**Acute Toxicity (Dermal):** Not classified

**Acute Toxicity (Inhalation):** Not classified

<b>Cyclohexane (110-82-7)</b>	
LD50 Oral Rat	12705 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 32880 mg/m <sup>3</sup> (Exposure time: 4 h)
<b>Ethyl acetate (141-78-6)</b>	
LD50 Oral Rat	5620 mg/kg
LD50 Dermal Rabbit	> 18000 mg/kg
LC50 Inhalation Rat	> 7348 mg/l/4h (calculated off of 6hr test results)
LC50 Inhalation Rat	4000 ppm/4h
<b>Acrylic acid (79-10-7)</b>	
LD50 Oral Rat	1337 mg/kg
LD50 Dermal Rabbit	640 mg/kg
LC50 Inhalation Rat	11.1 mg/l (Exposure time: 1 h)
LC50 Inhalation Rat	3.6 mg/l/4h
LC50 Inhalation Rat	2.75 mg/l/4h
<b>Titanium dioxide (13463-67-7)</b>	
LD50 Oral Rat	> 10000 mg/kg
LC50 Inhalation Rat	5.09 mg/l/4h
<b>Aluminum oxide (Al<sub>2</sub>O<sub>3</sub>) (1344-28-1)</b>	
LD50 Oral Rat	> 15900 mg/kg
LC50 Inhalation Rat	> 2.3 mg/l/4h
<b>Sodium hydroxide (1310-73-2)</b>	
LD50 Oral Rat	325 mg/kg
<b>White mineral oil, petroleum (8042-47-5)</b>	
LD50 Oral Rat	> 5000 mg/kg
<b>Carbon black (1333-86-4)</b>	
LD50 Oral Rat	> 8000 mg/kg
LC50 Inhalation Rat	> 4.6 mg/m <sup>3</sup> (Exposure time: 4 h)
<b>Isopropyl alcohol (67-63-0)</b>	
LD50 Dermal Rabbit	12956 mg/kg (16.4 mL/kg bw)
LC50 Inhalation Rat	> 10000 ppm (Exposure time: 6 h)

**Skin Corrosion/Irritation:** Not classified

**pH:** 8

**Serious Eye Damage/Irritation:** Not classified

**pH:** 8

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Suspected of causing cancer.

<b>Acrylic acid (79-10-7)</b>	
IARC group	3
<b>Titanium dioxide (13463-67-7)</b>	
IARC group	2B

# Jet Black Color Magic Black

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

US GHS SDS

<b>OSHA Hazard Communication Carcinogen List</b>	In OSHA Hazard Communication Carcinogen list.
<b>Carbon black (1333-86-4)</b>	
<b>IARC group</b>	2B
<b>OSHA Hazard Communication Carcinogen List</b>	In OSHA Hazard Communication Carcinogen list.
<b>Isopropyl alcohol (67-63-0)</b>	
<b>IARC group</b>	3

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** Prolonged exposure may cause irritation.

**Symptoms/Injuries After Skin Contact:** Prolonged exposure may cause skin irritation.

**Symptoms/Injuries After Eye Contact:** May cause slight irritation to eyes.

**Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** Suspected of causing cancer.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecology - General** : Not classified.

<b>Cyclohexane (110-82-7)</b>	
<b>LC50 Fish 1</b>	3.96 – 5.18 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
<b>EC50 - Crustacea [1]</b>	0.9 mg/l
<b>LC50 Fish 2</b>	23.03 – 42.07 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
<b>NOEC Chronic Algae</b>	0.94 mg/l
<b>Ethyl acetate (141-78-6)</b>	
<b>LC50 Fish 1</b>	220 – 250 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
<b>EC50 - Crustacea [1]</b>	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
<b>LC50 Fish 2</b>	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
<b>Acrylic acid (79-10-7)</b>	
<b>LC50 Fish 1</b>	222 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])
<b>EC50 - Crustacea [1]</b>	95 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>ErC50 (Algae)</b>	0.13 mg/l
<b>NOEC Chronic Algae</b>	0.016 mg/l
<b>Aluminum oxide (Al2O3) (1344-28-1)</b>	
<b>LC50 Fish 1</b>	> 100 mg/l
<b>EC50 - Crustacea [1]</b>	> 100 mg/l
<b>ErC50 (Algae)</b>	> 100 mg/l
<b>NOEC (Acute)</b>	> 50 mg/l
<b>Sodium hydroxide (1310-73-2)</b>	
<b>LC50 Fish 1</b>	45.4 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
<b>EC50 - Crustacea [1]</b>	40 mg/l
<b>White mineral oil, petroleum (8042-47-5)</b>	
<b>LC50 Fish 1</b>	> 10000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
<b>Carbon black (1333-86-4)</b>	
<b>EC50 - Crustacea [1]</b>	5600 mg/l (Exposure time: 24 h - Species: Daphnia magna)
<b>Isopropyl alcohol (67-63-0)</b>	
<b>LC50 Fish 1</b>	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
<b>EC50 - Crustacea [1]</b>	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>EC50 Other Aquatic Organisms 1</b>	1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
<b>LC50 Fish 2</b>	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
<b>EC50 Other Aquatic Organisms 2</b>	1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)

# Jet Black Color Magic Black

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
US GHS SDS

### 12.2. Persistence and Degradability

Jet Black Color Magic Black	
Persistence and Degradability	Not established.

### 12.3. Bioaccumulative Potential

Jet Black Color Magic Black	
Bioaccumulative Potential	Not established.
Cyclohexane (110-82-7)	
Partition coefficient n-octanol/water (Log Pow)	3.44
Ethyl acetate (141-78-6)	
BCF Fish 1	30
Partition coefficient n-octanol/water (Log Pow)	0.6
Acrylic acid (79-10-7)	
Partition coefficient n-octanol/water (Log Pow)	0.38 – 0.46 (at 25 °C)
White mineral oil, petroleum (8042-47-5)	
Partition coefficient n-octanol/water (Log Pow)	> 6
Isopropyl alcohol (67-63-0)	
Partition coefficient n-octanol/water (Log Pow)	0.05 (at 25 °C)

12.4. Mobility in Soil No additional information available

### 12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste Treatment Methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, and international regulations.

**Additional Information:** Container may remain hazardous when empty. Continue to observe all precautions.

**Ecology - Waste Materials:** Avoid release to the environment.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT Not regulated for transport

14.2. In Accordance with IMDG Not regulated for transport

14.3. In Accordance with IATA Not regulated for transport

## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

All components in this mixture are listed on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, have been exempted, are not listed, not disclosed due to CBI requirements or disclosure rules according to the relevant regulation.

Jet Black Color Magic Black	
SARA Section 311/312 Hazard Classes	Health hazard - Carcinogenicity
Cyclohexane (110-82-7)	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	1000 lb
SARA Section 313 - Emission Reporting	1 %
Ethyl acetate (141-78-6)	
CERCLA RQ	5000 lb
Acrylic acid (79-10-7)	
Subject to reporting requirements of United States SARA Section 313	

# Jet Black Color Magic Black

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
US GHS SDS

<b>CERCLA RQ</b>	5000 lb
<b>SARA Section 313 - Emission Reporting</b>	1 %
<b>Aluminum oxide (Al<sub>2</sub>O<sub>3</sub>) (1344-28-1)</b>	
Subject to reporting requirements of United States SARA Section 313	
<b>SARA Section 313 - Emission Reporting</b>	1 % (fibrous forms)
<b>Sodium hydroxide (1310-73-2)</b>	
<b>CERCLA RQ</b>	1000 lb
<b>Isopropyl alcohol (67-63-0)</b>	
Subject to reporting requirements of United States SARA Section 313	
<b>SARA Section 313 - Emission Reporting</b>	1 % (only if manufactured by the strong acid process, no supplier notification)

### 15.2. US State Regulations

<b>Cyclohexane (110-82-7)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
<b>Ethyl acetate (141-78-6)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
<b>Acrylic acid (79-10-7)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
<b>Titanium dioxide (13463-67-7)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List
<b>Aluminum oxide (Al<sub>2</sub>O<sub>3</sub>) (1344-28-1)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
<b>Sodium hydroxide (1310-73-2)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
<b>Carbon black (1333-86-4)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List
<b>Isopropyl alcohol (67-63-0)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

# Jet Black Color Magic Black

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
US GHS SDS

### SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

<b>Date of Preparation or Latest Revision</b>	: 04/01/2024
<b>Formula Identification Number</b>	: 40765
<b>Other Information</b>	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200].

#### GHS Full Text Phrases:


Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapor) Category 3
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 2	Carcinogenicity Category 2
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H290	May be corrosive to metals
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

# Jet Black Color Magic Black

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
US GHS SDS

<b>NFPA Health Hazard</b>	: 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.
<b>NFPA Fire Hazard</b>	: 1 - Materials that must be preheated before ignition can occur.
<b>NFPA Reactivity Hazard</b>	: 0 - Material that in themselves are normally stable, even under fire conditions.
<b>HMIS III Rating</b>	
<b>Health</b>	: 0 Minimal Hazard
<b>Flammability</b>	: 1 Slight Hazard
<b>Physical</b>	: 0 Minimal Hazard



*Legal disclaimer: Turtle Wax, Inc. All rights reserved.*

*This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular conditions or process. Such information is, to the best of our knowledge and belief, accurate and reliable as of the date issued. No warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the responsibility of the user or processor to satisfy themselves as to the suitability of such information for their own particular circumstances, conditions or use, including transportation, storage and disposal which are outside of our control.*

SDS US (GHS HazCom)