Product datasheet

LEDriving SLT C5W 6430

LED replacement lamp with a color temperature of up to 5,800 K
Modern and intense uniform illumination

Replaces all conventional C5W 24V lamp bases
Easy upgrade to LED technology with plug & play solution

Reliable OSRAM quality stands for less lamp replacements
4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for Festoon types

LEDriving SLT C5W replacement lamps offer a modern and intense light with a color temperature up to 5,800 Kelvin. These replacement lamps are suitable for all conventional C5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SLT lamps.These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

© 2026, OSRAM GmbH. All rights reserved.

Product datasheet

Technical data

Product information

Product type (off-road vs. on-road)	Off-road ≙ C5W
Application (Category and Product specific)	Mainly used for signal/ indicator/ interior applications

General Product Information

Global order reference	6430DWP

Electrical Data

Test voltage	28.0 V
Power input tolerance	±30 %
Nominal wattage	0 W
Nominal voltage	24 V

Photometric Data

Color temperature	5700 K
Luminous flux tolerance	±30 %
Light color LED	Cool white

Physical Attributes & Dimensions

Product weight	2.50 g
Length	30.5 mm
Lamp base	SV8.5-8
Diameter	10.8 mm

Lifetime Data

Lifespan Tc	3000 hr
Guarantee	4 years
Lifespan B3	1500 hr

Capabilities

Technology	LED

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Primary article identifier	4062172409742 | 4062172410717
Candidate list substance 1	Lead

© 2026, OSRAM GmbH. All rights reserved.

Product datasheet

CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	0fd2ac83-4fa2-4d27-8c07-aa485c674ae4 | e79a80ca-86f9-4cbf-a93d-2b08ac355d3e

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172409742	LEDriving SLT ≙C5W	Blister 1	95 mm x 17 mm x 135 mm	0.22 dm³	14.00 g
4062172409759	LEDriving SLT ≙C5W	Shipping carton box 5	142 mm x 64 mm x 104 mm	0.95 dm³	93.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

	File
	User instruction GPRS_Safety symbols instructions

Safety advice
Application advice:For more detailed application information and graphics please see product datasheet and user manual.

Application advice
For more detailed application information and graphics please see product datasheet.

Disclaimer
Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, OSRAM GmbH. All rights reserved.